
# Effect of Stream Restoration on the Water Quality of a North Carolina Stream

Dan Line
NCSU BAE Department

Funded by: NC DWQ 319 grant & NC DMS

#### **Stream Restoration**

- Extensive use
  - Many miles of stream restored
- Monitoring
  - Mitigation type: nearly all streams
  - Research type: few studies



#### FINAL RESTORATION PLAN HEATH DAIRY ROAD RESTORATION SITE RANDOLPH COUNTY, NORTH CAROLINA

Prepared for:

NORTH CAROLINA DEPARTMENT OF ENVIRONMENT

AND NATURAL RESOURCES

ECOSYSTEM ENHANCEMENT PROGRAM


RALEIGH, NORTH CAROLINA

NCDENR D06017S

SCO# 040633101

http://deq.nc.gov/about/divisions/mitigation-services/dms-projects




















## **WQ Monitoring**

- Rainfall
  - Recording 8 in. gage
- Discharge
  - Integrated Doppler flowmeter on sampler
  - Manual discharge measurements (growing and dormant vegetation)
- Water Quality
  - Flow-proportional storm sampling (TKN, NH<sub>3</sub>-N, NOx-N, TP, TSS
  - Quarterly grab sampling







# **Load/Export Rates**

Site	Rain	Q	TKN	NH <sub>3</sub> -N	NO <sub>x</sub> -N	TP	TSS		
	mm/yr	mm/yr	kg/ha yr						
NBr-up	1180	270	11.7	1.32	0.74	3.44	1922		
NBr-dn	1180	274	11.6	1.07	0.92	3.28	2120		
		ns	ns	-19	+24	ns	ns		
ns= not si	gnificantly	different							

Duration of monitoring: 1.57 yr Bankfull Q exceeded: 5 times

Daily mean Q= 1540 L/min or 0.91 cfs

# Load Rates (w/o Bankfull Q)

Site	Q	TKN	NH <sub>3</sub> -N	NO <sub>x</sub> -N	TP	TSS			
	m³/wk	kg/wk							
NBr-up	7780	31.6	4.2	2.4	9.3	4760			
NBr-dn	7940	30.3	3.3	3.0	8.7	4853			
		4.1	-21	+25	ns	ns			
ns= not significantly different per paired t test									

## **Summary/Conclusion**

- Monitoring up/downstream of 134 m long restored section of North Branch
  - No change in TKN, TP, TN, and TSS
  - NH<sub>3</sub>-N decrease 19%; NOx-N increased 24%
- No effect on TN, TP, and TSS loads in stream

### **Questions?**

Transactions of the ASABE 58(6): 1547-1557